JUL-07-08 15:20

## Amendments to the Claims

This listing of claims will replace all prior versions and listings of claims in the applications.

# Listing of Claims

- (Currently Amended) A structural panel for use in building construction, 1. comprising
  - a first metal skin having a first face;
  - a second metal skin having a first face spaced apart from the first skin first face;
- a reinforcing member having a first surface fixed to the first skin first face and a second surface fixed to the second skin first face;
- a first foam piece having a first surface fixed to the first skin first face, a second surface fixed to the second skin first face, and a third surface abutting a third surface of the reinforcing member; and
- a second foam piece having a first surface fixed to the first skin first face, a second surface fixed to the second skin first face, and a third surface abutting a fourth surface of the reinforcing member.
- (Original) The structural panel of claim 1, further comprising a first 2. interlocking edge and a second interlocking edge, the first interlocking edge configured to interlock with a second interlocking edge of a second panel.
- (Previously Presented) The structural panel of claim 2, wherein the first and the second interlocking edges are formed from the first and second skins.
- (Original) The structural panel of claim 2, wherein the reinforcing 4. member is substantially parallel to the first interlocking edge.
- 5. (Original) The structural panel of claim 1, wherein the first and second foam pieces are fixed to the reinforcing member.

Page 2 of 10

DO NOT ENTER. PD 07/13/06

- 6. (Original) The structural panel of claim 1, wherein the first skin comprises aluminum.
- 7. (Original) The structural panel of claim 1, wherein the first skin comprises steel.
- 8. (Original) The structural panel of claim 1, wherein the reinforcing member comprises metal.
- (Original) The structural panel of claim 8, wherein the width between the third and fourth surfaces of the reinforcing member is greater than 0" and less than 0.40".
- 10. (Original) The structural panel of claim 1, wherein the reinforcing member comprises sheet metal.
- 11. (Original) The structural panel of claim 1, wherein the reinforcing member comprises a honeycomb material.
- 12. (Original) The structural panel of claim 11, wherein the reinforcing member comprises a paper honeycomb.
- 13. (Previously Presented) The smucrural panel of claim 11, wherein the reinforcing member comprises a NOMEX honeycomb.
- 14. (Original) The structural panel of claim 11, wherein the reinforcing member comprises an aluminum honeycomb.
- 15. (Original) The structural panel of claim 11, wherein the width between the third and fourth surfaces of the reinforcing member is greater than 0" and less than 1.25".

### Page 3 of 10

16. (Original) The structural panel of claim 1, wherein the reinforcing member comprises an aluminum foam.

### 17. (Cancelled)

- 18. (Currently Amended) The structural panel of claim 1 [[17]], wherein the third surface of the first foam piece is bonded to the third surface of the reinforcing member.
- 19. (Currently Amended) The structural panel of claim 1, further comprising a third foam piece extending between the first skin and the second skin; and a second reinforcing member extending between the first skin and the second skin disposed between the second foam piece and the third foam piece.
  - 20. (Original) The structural panel of claim 1, further comprising
- a second reinforcing member extending between the first skin and the second skin, having a first surface facing the first foam piece and a second exposed surface opposite the first surface; and
- a third reinforcing member extending between the first skin and the second skin, having a first surface facing the second foam piece and a second exposed surface opposite the first surface.
  - 21. (Currently Amended) A method of making a panel, comprising providing a first piece of foam; providing a first reinforcing member; providing a second piece of foam;

forming a first planar surface including a surface from each of the first piece of foam, the first reinforcing member, and the second piece of foam;

forming a second planar surface including a surface from each of the first piece of foam, the first reinforcing member, and the second piece of foam;

providing a first metal skin;

providing a second <u>metal</u> skin; applying [[a]] <u>the</u> first <u>metal</u> skin to the first planar surface; and applying [[a]] <u>the</u> second <u>metal</u> skin to the second planar surface.

- 22. (Original) The method of claim 21, further comprising the step of positioning the first reinforcing member between the first piece of foam and the second piece of foam.
- 23. (Original) The method of claim 21, further comprising the step of forming the first surface by aligning the first and second pieces of foam and the first reinforcing member.
- 24. (Original) The method of claim 23, further comprising the step of forming the first surface by cutting first and second pieces of foam and the first reinforcing member.

### 25. (Canceled)

26. (Original) The method of claim 21, further comprising the step of providing a second reinforcing member,

wherein the step of forming a first planar surface further comprises forming the first planar surface including a surface from the second reinforcing member, and

wherein the step of forming a second planar surface further comprises forming the second planar surface including a surface from the second reinforcing member.

27. (Original) The method of claim 21, further comprising the step of providing a third piece of foam,

wherein the step of forming a first planar surface further comprises forming the first planar surface including a surface from the third piece of foam, and

wherein the step of forming a second planar surface further comprises forming the second planar surface including a surface from the third piece of foam.